

taken 1950 - Fund cherked 1951 - Found 1961

16,600 to tight and based on Kentucky coordinate system, south John

1000 metre or set al Transsers Mercator and ticks, zone 17, so as as folia

Mapped, edited, and published by the Geological Survey

Landslides and related features interpreted from aerial photographs:

1:80,000 (black and white) 1977

Photointerpretation and field check 1978,9 This report is preliminary and has not been reviewed for conformity with U. S. Geological Survey editorial standards. Data on location of strip mines in part from: Prichard, George E. and Johnston, John E., 1963, Geology of the Jackson Quadrangle, Kentucky: U. S. Geological Survey Geologic Quadrangle Map GQ-205, scale 1:24,000.

ACTIVE OR RECENTLY ACTIVE LANDSLIDE Complex landslide composed of earthflow, debris slide, earth and rock slump. Identified from historical records, and from scars, debris and other field evidence. Ground extremely unstable; sliding accelerated by excavation, loading and changes in drainage conditions. May include areas with several active slides too small to be shown separately. Questioned where doubtful.

OLD LANDSLIDE Area of extensive hummocky ground caused by earthflow and earth and rock slump. Lacks clear evidence of active sliding. Relatively stable in natural, undisturbed state, generally not affected by small structures properly sited in areas away from the edge of the toe; can be reactivated by extensive, rapid excavation, loading, and changes in ground water and surface water conditions. Area of old landslide probably includes recent ones not identified from field evidence or otherwise documented. Upslope boundary of landslide generally defined by modified scarp, but downslope (toe) may be gradational and not well defined. Questioned where doubtful.

COMBINATION LANDSLIDE Area of recent and old slides in which individual slides are not identified.

COLLUVIAL SLOPE

Valley wall along major streams with slope as steep as 40° (85%); stony, clayey silt soil up to 50 ft. (15 m) thick; commonly buttressed by a terrace or bench at the toe of the slope; very susceptible to sliding by cutting of toe area, removal of terrace or bench, and overloading: slide commonly activated without apparent cause.

LANDSLIDES AND RELATED FEATURES

SCALE 1.24 000

CONTOUR INTERVAL 20 FEE

NATIONAL GEODETIC VERTICAL DATUM OF 19.9

OF THE JACKSON, KY. QUADRANGLE

William F. Outerbridge 1982

U.S. Geological Survey

OPEN FILE MAP 82-51 (E-5)

individually.

COLLUVIAL SLOPES WITH LANDSLIDES Landslides too small or obscure to map

AREAS SUSCEPTIBLE TO DEBRIS FLOWS AND DEBRIS

AVALANCHES

Primarily shallow, narrow ravines and chutes with accumulation of stony colluvium generally 10 ft. (3 m) or less in thickness; susceptible to rapid movement during intense rainfall. Most ravines and chutes designated show evidence of former debris flows and avalanches. Symbol & designates historical debris flow or debris avalanche.

AREAS SUSCEPTIBLE TO ROCKFALL Steep, locally vertical, natural and man-made slopes and cliffs, 15 ft. (4.5 m) or more high; formed dominantly of sandstone, limestone, sandy shale, mudstone and claystone. Interbedded mudstone, claystone and shale weather rapidly leaving sandstone and limestone rock faces unsupported.

SOIL AND ROCK SUSCEPTIBLE TO LANDSLIDING Soil and rock similar to that involved in landslides elsewhere in map area; primarily areas underlain by claystone, mudstone and shale associated with other rock types. Rock weathers rapidly on exposure forming clayey soil highly susceptible to sliding. Includes coves (U-shaped, shallow valleys) containing thick layers of clayey soil that are very susceptible to sliding where excavation breaks continuity of slope and where overloaded by artificial fill.

AREAS LEAST PRONE TO LANDSLIDES

Map areas in which no patterns or symbols are shown; primarily valley floors, ridge tops and broad benches; modification by excavation and fill may lead to local landslides.

The first four digits of the open file number designate the specific 1:250,000 scale map sheet of which this quadrangle is a part. The last two digits designate the position of the quadrangle in a subdivision of the 1:250,000 scale map based on rows and tiers shown in the diagram to the right. The location of this quadrangle is shown by the black square.

JACKSON, KY. N3/30 - W8322 % 75

1961

NOTE Information shown is intended as a general guide to ground conditions as of the date of field check. Additional landslides and rockfalls should be anticipated in all map units. The map unit depicts the dominant condition in the area delineated and variations in slope stability may occur at any point in the unit. This map is suitable for general planning purposes and as a supplement to more detailed studies for site selection. The map cannot be used as a substitute for detailed geologic and engineering investigations to establish design and construction criteria of specific sites. Some symbols may not appear on this map because the description is applicable to a series of maps.

MAN-MADE FEATURES Strip mines (combination of letter symbols

s f

indicates complex formed of more than one type of strip mine)

furrowed with high wall

bench with high wall sh

multiple furrows and multiple benches hilltop removed 55

reclaimed by grading srg reclaimed by secondary use

sru

regraded in part, high wall remains

identified on aerial photographs; not classified in field check

not burnt nor on fire

burnt rbb

burning

sludge

rbs Quarries

rbd

a/s

Coal refuse banks

quarry site spoil bank, quarry waste

Gravel pits

site of gravel pit

Slides in man-made features af earth flow in fill

earth flow in coal refuse JENKINS 1°x2° SHEET

earth flow in strip castings

